NS 35/ 7,5 V2A UNPERF 2000MM - DIN rail, unperforated

0801377

https://www.phoenixcontact.com/us/products/0801377

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Stainless steel V2A, uncoated, Standard profile, color: silver-colored

Commercial data

Item number	0801377
Packing unit	25 m
Minimum order quantity	50 m
Sales key	BE72
Product key	BE7238
GTIN	4017918138790
Weight per piece (including packing)	660 g
Weight per piece (excluding packing)	660 g
Customs tariff number	72224050
Country of origin	DE

NS 35/ 7,5 V2A UNPERF 2000MM - DIN rail, unperforated

0801377


https://www.phoenixcontact.com/us/products/0801377

Technical data

Product properties

Product type	DIN rail

Dimensions

Dimensional drawing	
Width	35 mm
Depth	7.5 mm
Length	2000 mm

Material specifications

Color	silver-colored
Material	Stainless steel V2A
Coating	uncoated

Standards and regulations

Connection in acc. with standard	IEC / EN
Tests	acc. to EN 60715


Electrical tests


Short-time withstand current

Equivalent E-Cu cross-section	16 mm²
Short-time current resistance 1s	1.92 kA

Drawings

Dimensional drawing





Classifications

ECLASS

ECLASS-13.0	27400602
ECLASS-15.0	27400602

ETIM

ETIM 10.0	EC001285

UNSPSC

UNSPSC 21.0	39121700

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

EF3.1 Climate Change

CO2e kg	4.585 kg CO2e

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com