# VS-08-ST-H21P-RJ45 - RJ45 male insert

1404388

https://www.phoenixcontact.com/us/products/1404388

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

CRIMP



RJ45 male insert, CAT6, 8-pos., shielded, IDC pierce connection, for AWG 27 litz wires ... 24, with strain relief

## Your advantages

- Reliable 360° shield contact due to the proven crimp connection
- Easy installation with a crimping tool
- Pin insert for V.06 sleeve housing VS-08-T-H-RJ45/IP67

## Commercial data

| | |
|---|---|
| Item number | 1404388 |
| Packing unit | 5 pc |
| Minimum order quantity | 5 pc |
| Sales key | AB10 |
| Product key | ABNAAG |
| GTIN | 4046356313230 |
| Weight per piece (including packing) | 4.4 g |
| Weight per piece (excluding packing) | 4.005 g |
| Customs tariff number | 85366990 |
| Country of origin | TW |

# Technical data

## Product properties

| | |
|---|---|
| Product type | Data connector (cable side) |
| Type | RJ45 |
| Number of positions | 8 |
| Connection profile | RJ45 |
| No. of cable outlets | 1 |
| Shielded | yes |
| Cable outlet | straight |
| Positions/contacts | 8P8C |

### Insulation characteristics

| | |
|---|---|
| Overvoltage category | I |
| Degree of pollution | 2 |

## Electrical properties

| | |
|---|---|
| Rated voltage (III/3) | 72 V (DC) |
| Rated surge voltage | 330 kV |
| Rated current | 1 A |
| Contact resistance | < 20 mΩ (Contact) |
| | < 100 mΩ (shield) |
| Frequency range | to 250 MHz |
| Insulation resistance | > 500 MΩ (100 V DC) |
| Nominal voltage $U_N$ | 48 V |
| Nominal current $I_N$ | 1 A |
| Contact resistance per contact pair | < 20 Ω |
| Contact resistance | > 10 mΩ (Wire – IDC) |
| Transmission medium | Copper |
| Transmission characteristics (category) | CAT6 |

## Connection data

### Connection technology

| | |
|---|---|
| Connection method | Crimp connection |
| Connection cross section AWG | 27 ... 24 (flexible) |
| Conductor cross-section | 0.11 mm² ... 0.22 mm² (flexible) |
| Cable outlet, angle | 180 |

## Interfaces

| | |
|---|---|
| Signal type/category | Ethernet CAT6 |

## Dimensions

| | |
|---|---|
| Width | 11.7 mm |
| Height | 14 mm |

| | |
|---|---|
| Length | 30.2 mm |

## Material specifications

| | |
|---|---|
| Color | red |
| Flammability rating according to UL 94 | V2 |
| Contact material | Phosphor bronze |
| Contact surface material | Au/Ni |
| Contact carrier material | PC |
| Locking latch material | PC |
| Material for screw connection | PA |

## Cable/line

| | |
|---|---|
| External cable diameter | 6.6 mm |
| Wire diameter including insulation | 0.9 mm ... 1 mm |
| Test voltage Core/Core | 1000 V |
| Test voltage Core/Shield | 1500.00 V |

## Mechanical properties

Mechanical data

| | |
|---|---|
| Insertion/withdrawal cycles | ≥ 750 |
| Insertion force per signal contact | < 20.00 N |
| Extraction force per signal contact | < 20 N |

## Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -25 °C ... 60 °C |

## Mounting

| | |
|---|---|
| Mounting type | Crimp connection |

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-15.0 | 27440114 |
| ECLASS-13.0 | 27440114 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC002636 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121400 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

EF3.1 Climate Change

| | |
|---|---|
| CO2e kg | 0.045 kg CO2e |

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com