# EC 1 12DC/1A S-R - Electronic circuit breaker

3000760

https://www.phoenixcontact.com/us/products/3000760

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Electronic circuit breaker, reset input and status output, nominal current: 1 A

ELEKTROGERÄTE RÜCKNAHME

## Commercial data

| | |
|---|---|
| Item number | 3000760 |
| Packing unit | 6 pc |
| Minimum order quantity | 6 pc |
| Sales key | CL04 |
| Product key | CLA131 |
| GTIN | 4046356708548 |
| Weight per piece (including packing) | 70.25 g |
| Weight per piece (excluding packing) | 68.1 g |
| Customs tariff number | 85362010 |
| Country of origin | DE |

## Technical data

### Product properties

| | |
|---|---|
| Product type | Device circuit breakers |
| Product family | EC-E |
| Type | DIN rail module, one-piece |
| Number of positions | 1 |

### Electrical properties

| | |
|---|---|
| Maximum load current | 1 A (100 % Duty Cycle, 40 °C) |
| | 1 A (100 % Duty Cycle, 50 °C) |
| Service life electrical | 10000 |

General

| | |
|---|---|
| Fuse | electronic |

### Connection data

| | |
|---|---|
| Maximum load current | 1 A (100 % Duty Cycle, 40 °C) |
| | 1 A (100 % Duty Cycle, 50 °C) |

Line+ / LOAD+ /0V

| | |
|---|---|
| Connection method | Screw connection |
| Screw thread | M4 |
| Tightening torque | 1.5 ... 1.8 Nm |
| Stripping length | 10 mm |
| Conductor cross-section rigid | 0.5 mm² ... 10 mm² |
| Conductor cross-section flexible | 0.5 mm² ... 10 mm² |
| 2 conductors with same cross section, rigid | 0.5 mm² ... 4 mm² |
| 2 conductors with same cross section, flexible | 0.5 mm² ... 4 mm² |
| Nominal current | 1 A |
| Nominal voltage | 12 V DC |

Signal connections

| | |
|---|---|
| Connection method | Screw connection |
| Screw thread | M3 |
| Tightening torque | 0.5 ... 0.6 Nm |
| Conductor cross-section flexible | 0.25 mm² ... 2.5 mm² |

### Dimensions

| | |
|---|---|
| Width | 12.5 mm |
| Height | 80 mm |

### Material specifications

| | |
|---|---|
| Color | black (RAL 9005) |

## Environmental and real-life conditions

### Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 60 °C (ordinary locations) |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

## Mounting

| | |
|---|---|
| Mounting type | DIN rail: 35 mm |

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/3000760

**UL Recognized**
Approval ID: FILE E 317172

**DNV GL**
Approval ID: TAE00002HC

**cULus Recognized**
Approval ID: E123528

**cULus Listed**
Approval ID: E123528

**UL Recognized**
Approval ID: FILE E 324415

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27140401 |
| ECLASS-15.0 | 27140401 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC003538 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121400 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 7(a), 7(c)-I |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-25 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | d1e15dbe-7bf5-4f67-8370-ae55fe3052b7 |


Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com



Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com